



Series: CIRIL In-ground Lamps	Light color(s): warm white, cool white, blue
Model(s): CIRIL 200 Uni	Light distribution: diffuse
Reference(s): 5320	Luminous power (typ.): ww 48 cd/ cw 82 cd/ blue 22 cd
Dimensions: Ø 200 mm, h = 72 mm	IP code (IEC 60529): IP 66
Color(s): silver	Material(s): Aluminum, hard glass
Safety class (IEC 60417): III	Connection: 1 m cable.
Electrical data: 12 V DC, 3.5 W	Operating temperature: -40°...55°C Storage temperature: -40°...90°C
Usage: To mark, guide or as a decoration in indoor and outdoor use.	Remarks: When installed horizontal and flush to the ground, the lamps can bear the weight of common road vehicles with air-filled tires at a speed of up to 10 km/h.
Description: Corrosion-resistant in-ground lamp of strong anodized aluminum and 12 mm tempered frosted glass with ceramic anti-slip coating. Lighting with the latest premium HB LEDs.	Accessories: Power supplies # 6008...6102 LED-Dimmer
Installation: Direct installation into concrete, stone, marble, wood etc., then grouting of the small remaining joint of about 3 mm with silicone or similar. Result: a rimless and unobtrusive integration into the surrounding flooring.	
Revision: 12.18	