





| Series: | Light color(s): |
|---|--|
| LED Guides, In ground Lamps | warm white, cool white, blue, green, yellow, red |
| Model(s): | Light distribution: |
| LED-Guide 65D | diffuse |
| Reference: | Luminous power (typ.): |
| 5165 | ww 5 cd/ cw 6.3 cd/ blue 0.9 cd/ |
| | green 3.5 cd/ yellow 1.6 cd/ red 1.6 cd |
| Dimensions: | IP code (IEC 60529): |
| Ø 65 mm, h = 35 mm | IP67 |
| Color(s): | Material(s): |
| silver | Stainless steel, aluminum, hard glass |
| Safety class (IEC 60417): | Connection: |
| III - | 0.5 m cable. |
| Electrical data: | Operating temperature: -40°55°C |
| 12 V DC, 0.4 W | Storage temperature: -40°90°C |
| Usage: | Remarks: |
| To mark, guide or as a decoration in indoor and | When installed horizontal and flush to the ground, |
| outdoor use. | the lamps can bear the weight of common road |
| | vehicles with air-filled tires at a speed of up to |
| | 10 km/h. |
| Description: | Accessories: |
| Stainless steel V2A LED light for ground and wall | Power supplies # 60086102 |
| mounting with glue. Equipped with high-perfor- | |
| mance LEDs and a 25 mm tempered glass sealed | |
| with glue to ensure waterproofness. | |
| - · | |
| | |
| Installation: | |

Revision: 12.18

Disclaimer: Technical data are subject to modification and delivery subject to availability. Any liability for the completeness, topicality and correctness of the data and illustrations shall be excluded. Designa ions may be trademarks and/or subject to copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. All rights reserved by CHAMP Licht Rolf Winter, 83278 Traunstein, Germany.