Data sheet







| Series: | Light color(s): |
|--|--|
| LED Guides, In ground Lamps | warm white or cool white |
| | other colors on request |
| Model(s): | Light distribution: |
| LED-Guide 66D | diffuse |
| Reference: | Luminous power (typ.): |
| 5166 | ww 75 lm / cw 105 lm |
| Dimensions: | IP code (IEC 60529): |
| Ø 65 mm, h = 35 mm | IP67 |
| Color(s): | Material(s): |
| silver | Stainless steel, aluminum, hard glass |
| Safety class (IEC 60417): | Connection: |
| III | 1 m cable. |
| Electrical data: | Operating temperature: -40°55°C |
| 12 V DC,1.2 W | Storage temperature: -40°90°C |
| Usage: | Remarks: |
| To mark, guide or as a decoration in indoor and | When installed horizontal and flush to the ground, |
| outdoor use. | the lamps can bear the weight of common road |
| | vehicles with air-filled tires at a speed of up to |
| | 10 km/h. |
| Description: | Accessories: |
| Stainless steel V2A LED light for ground and wall | Power supplies # 60086102 |
| mounting with glue. Equipped with high-power LED | |
| and a 25 mm tempered glass sealed with glue to | |
| ensure waterproofness. | |
| Installation: | |
| Mounting with 3 screws into holes of 35 mm in any material like wood, stone, concrete etc. | |
| | |
| | |
| | |

Revision: 12.18