



<b>Series:</b>  <b>LED Lights</b>	<b>Light color(s):</b> warm white, cool white.
<b>Model:</b> Jill 1W 12V	<b>Light distribution (FWHM):</b> 120° via special optics
<b>Reference:</b> 4278	<b>Luminous power:</b> ww 75 lm, ~ 3000K / cw 105 lm, ~ 6000K
<b>Dimensions:</b> Ø 50 x 10 mm height	<b>IP code (IEC 60529):</b> IP 65
<b>Color(s):</b> silver	<b>Material(s):</b> Aluminum, casting compound
<b>Safety class (IEC 60417):</b> III	<b>Connection:</b>  Strands 1 m
<b>Electrical data:</b> 12 VDC, 1.2 W	<b>Operating temperature:</b> -40...55 °C <b>Storage temperature:</b> -40...90 °C
<b>Usage:</b> The extremely long service life and the very low heat generation due to the high efficiency predestine this spotlight for many commercial applications, particularly showcases, furnitures, aisles, car park, displays a.s.o.	<b>Remarks:</b> Driver electronic included for easy installation anywhere even in vehicles.
<b>Description:</b> Small surface-mounted LED lamp made of anodized aluminium and the latest high-power LED, completely cast in.	<b>Accessories:</b> Power supplies # 6008...6061 LED-Dimmer # 6585 / 6586
<b>Installation:</b> For mounting there are two holes for countersunk screws up to 3.5 mm diameter with a distance of 36 mm. Avoid ingress of water into the strands!	
Revision: 10.19	



<b>Serie:</b> <b>LED Lights</b>	<b>Lichtfarbe:</b> warm white, cool white
<b>Modell:</b> Jill 1W 12V	<b>Lichtverteilung (FWHM):</b> 120° durch Speziallinse
<b>Artikelnummer:</b> 4278	<b>Lichtstärke (typ.):</b> ww 75 lm, ~ 3000K / cw 105 lm, ~ 6000K
<b>Abmessungen:</b> Ø 50 x 10 mm Höhe	<b>IP Code (IEC 60529):</b> IP 65
<b>Farbe:</b> silber	<b>Material:</b> Aluminium, Vergussmasse
<b>Schutzklasse (IEC 60417):</b> III	<b>Anschluss:</b> Litzen 1 m
<b>Elektrische Daten:</b> 12 VDC, 1.2 W	<b>Arbeitstemperaturen:</b> -40°...55°C <b>Lagertemperaturen:</b> -40°...90°C
<b>Anwendung:</b> Die extrem lange Lebensdauer und die sehr geringe Wärmeentwicklung durch den hohen Wirkungsgrad prädestinieren diesen Strahler für viele kommerzielle Anwendungen, insbesondere Vitrinen, Möbel, Gänge, Parkhäuser, Displays etc.	<b>Bemerkungen:</b> Inklusive Treiberelektronik für eine einfache Installation überall, auch in Fahrzeugen.
<b>Beschreibung:</b> Kleine Anbau-LED-Leuchte aus eloxiertem Aluminium und modernste Hochleistungs-LED, komplett eingegossen.	<b>Zubehör:</b> Netzteile # 6008...6061 LED-Dimmer # 6585/ 6586
<b>Installation:</b> Für die Montage sind zwei Löcher vorhanden für Senkkopfschrauben bis 3,5 mm Ø mit einem Abstand von 36 mm. Das Eindringen von Wasser in die Litzen ist zu vermeiden!	
Ausgabe: 10.19	